





UFO-X DIMMABLE HIGH BAYS



Dimensions



CODE	DESCRIPTION	LUMEN OUTPUT	LM/W	CRI	POWER FACTOR	DIMENSIONS (Ø X H / L X W X D MM)	WEIGHT (KG)
UFOX100-40	UFO-X DIMMABLE HIGH BAY 100W LED 4000K BLACK	13,000 lm	130	>80	≥0.95	252 x 127	2.0
UFOX100-65	UFO-X DIMMABLE HIGH BAY 100W LED 6500K BLACK	13,000 lm	130	>80	≥0.95	252 x 127	2.0
UFOX150-40	UFO-X DIMMABLE HIGH BAY 150W LED 4000K BLACK	19,500 lm	130	>80	≥0.95	252 x 127	2.0
UFOX150-65	UFO-X DIMMABLE HIGH BAY 150W LED 6500K BLACK	19,500 lm	130	>80	≥0.95	252 x 127	2.0
UFOX200-40	UFO-X DIMMABLE HIGH BAY 200W LED 4000K BLACK	26,000 lm	130	>80	≥0.95	252 x 127	2.0
UFOX200-65	UFO-X DIMMABLE HIGH BAY 200W LED 6500K BLACK	26,000 lm	130	>80	≥0.95	252 x 127	2.0
HLBMS	HIGH BAY MICROWAVE SENSOR	-	-	-	-	72 x 59	0.23
HLBMS-RC	REMOTE CONTROL FOR HIGH BAY MICROWAVE SENSOR	-	-	-	-	116 x 53 x 12	0.03
COMHBMSB-2	MICROWAVE SENSOR BRACKET FOR HLBMS	-	-	-	-	-	0.03





UFO-X DIMMABLE HIGH BAYS


Description

The new UFO-X Dimmable High Bays are made from aluminium & tempered glass, have a 4K surge protection and have a higher efficacy of 130lm/W making them suitable for a wide range of applications.

Key Features

- Improved efficacy 130lm/W
- 4K Surge protection as standard
- LED Lifetime 50,000hrs
- 1-10V Dimmable as standard
- Fully adjustable microwave sensor available with optional hand held remote control
- Made from aluminium & tempered glass
- Working Temperature -30°C to 45°C

Photometric Light Distribution Curve



- Wattage: 150W
- Lumen Output: 19,500lm
- LOR: 100%

Maximum Fittings Per Circuit

Automatic Circuit Breaker Type (ACB)	B6	B10	B13	B16	B20	C10	C13	C16	C20
Rated current (Ampere)	6A	10A	13A	16A	20A	10A	13A	16A	20A
Cable Size (mm ²)	1.5mm ²	1.5mm ²	1.5mm ²	1.5mm ²	2.5mm ²	1.5mm ²	1.5mm ²	1.5mm ²	2.5mm ²
UFOX100-40/65	3	5	7	8	11	9	11	14	18
UFOX150-40/65	3	5	7	8	10	9	11	14	18
UFOX200-40/65	1	3	5	6	7	6	8	10	13