

# SPECIFICATION SHEET

## LED CIRCULAR PANELS



The LED Circular Panels are suitable for educational providers and residential areas, are supplied with fixed output as standard and dimmable drivers are available to order separately if required.

### Applications:

- Educational providers • Residential • Retail



Image shown SP20W-40


### Specification

<b>LED:</b>	30-100pcs of SMD 2835
<b>Material:</b>	Aluminium and polycarbonate
<b>Guarantee:</b>	3 Years
<b>Life Expectancy:</b>	30,000 Hours
<b>Working Temperature:</b>	-20°C - 45°C
<b>Power Factor:</b>	>0.9
<b>Beam Angle:</b>	120°
<b>CRI:</b>	80 Ra

### Additional Information

- Emergency conversion (EMLEDKIT2) available.
- EMLEDKIT2 - 156-160lm in emergency mode.
- EMLEDKIT3 - 235-240lm in emergency mode.
- Phase cut dimming drivers available to order separately:SPS-DR6, SPS-DR12, SPS-DR15, SPS-DR18, SPS-DR20
- White finish.

### Dimensions



Code	Wattage	Colour Temperature	Lumen Output	Dimensions (Ø x D mm)	Cut out (Ø)
SP6W-30	6W	3000K	470lm	120 x 13	105
SP6W-40	6W	4000K	470lm	120 x 13	105
SP6W-60	6W	6000K	470lm	120 x 13	105
SP12W-30	12W	3000K	930lm	170 x 13	155
SP12W-40	12W	4000K	930lm	170 x 13	155
SP12W-60	12W	6000K	930lm	170 x 13	155
SP15W-30	15W	3000K	1170lm	190 x 13	180
SP15W-40	15W	4000K	1170lm	190 x 13	180
SP15W-60	15W	6000K	1170lm	190 x 13	180
SP18W-30	18W	3000K	1450lm	225 x 13	210
SP18W-40	18W	4000K	1450lm	225 x 13	210
SP18W-60	18W	6000K	1450lm	225 x 13	210
SP20W-30	20W	3000K	1600lm	240 x 13	225
SP20W-40	20W	4000K	1600lm	240 x 13	225
SP20W-60	20W	6000K	1600lm	240 x 13	225